


# Lumalex – 4FT & 6FT X 4” Panel



## Description

Model No.	<i>L44P-40K-20-4 L44P-50K-20-4, L44P-40K-30-6 L44P-50K-30-6</i>
Actual Size	<i>47.8" x 4" x 1.95" (incl JB) 47.8" x 5" x 1.95" (incl JB) 71.73" x 4" x 1.95" (incl JB) 71.73" x 5" x 1.95" (incl JB)</i>
Power	<i>20w, 30w, 110-277v</i>
CCT	<i>3500k, 4000k</i>
CCT	<i>5000k</i>
Luminous(lm)	<i>2100, 2770</i>
Lighting Effect	<i>up to 110 lm/w</i>
CRI	<i>&gt;80</i>
Power Factor	<i>&gt; 0.95</i>
Input Voltage	<i>110 – 277v</i>
Driver Output Voltage	<i>27 – 42v, 1.5A</i>
Work Temp	<i>-20°C to +50°C</i>
Beam Angle	<i>120°</i>
Dimmable	<i>0 – 10v</i>
IP Rating	<i>Damp Rated</i>
Lifespan	<i>50,000 Hours</i>
Warranty	<i>5 Years</i>

## Product Advantages

- New architectural design, linear style in 4ft and 6ft lengths
- Significant saving in power consumption and costs
- Minimal maintenance costs (materials and labour)
- Minimal heat generation
- No flicker. Significant reduction in eye strain
- Engineered optic design producing even light distribution with no hot spots.

## Certifications:

